Limited Series

Page 5





Select 42

It is big and it is stylish. The Select 42 is a 42" flush clean face fireplace that comes complete with porcelain panels and deluxe system as all of our limited line of fireplaces do. However, the Select 42 also showcases our new "traditional" style log set and our revamped burner with increased flame. It is a good looking fireplace and fully loaded!

Media: Traditional Log Set

Select High 30,000BTU's Low 22,000BTU's Framing Dim: 43" H X 45-3/4" W X 19-1/2" D Internal Ceiling = 66" Mantle Height = 50" * Safety Screen buit into Surround

Options and Accessories See Bottom of Page

-Deluxe System Only

-Porcelain Panels Included

OD2000 Linear 45 Outdoor

Rock and Glass

Warm up your backyard and maximize your outdoor experience with the OD2000 linear 45 outdoor fireplace. At 40,000 BTU's it will definitely take the chill off and the modern design will class up your backyard.

The OD2000 is completely stainless steel built fireplace from top to bottom, it is vent free for ease of installation and the stainless cover (included) will keep it protected for those days when it is not in use.

*Certified for wood framing.

OD2000 High 40,000BTU's Low 29,000BTU's Framing Dim 31" H X 47-3/8" W X 16" D Internal Ceiling = 48" Mantel Height = 42"

































Large Log #2

Dimensional Chart and Features



Model	BTU's		Vent Height		eight	Width		Depth		Viewing Area		Efficiency	
	Natural Gas	Propane		Actual	Framing	Actual	Framing	Actual	Framing	Height	Width	EnerGuide	
Coloot 12	Hi 30,000	29,000	Top	36"	43"	40-3/4"	45-3/4"	17-1/2"	19-1/2"	22 4/20	2" 34-1/4" 67.1	67.450/	
Select 42	Lo 22,000	19,500	4" & 7"							23-1/2		67.15%	

Surrounds: Standard Features: Clean Face Design - 30,000BTU Full Deluxe System see page 5 Porcelain Liner Tempered Glass Traditional Log Set

 Basic Black 3 Sided Driftwood & Media Kits · Basic Stainless 3 Sided

Ch	ampion
-	and I

	Ins
	Standard
1	see page
01	



Model	BTU's		BTU's Vent Height		Width		Depth		Viewing Area		Efficiency	
	Natural Gas	Propane		Actual	Min	Actual	Min	Actual	Min	Height	Width	EnerGuide
Incort	Hi 26,000	23,000	Top	20.040*	20.4/4"	20.420*	27"	10 015"	16 1/4**	16"	25"	CO 200/
Insert	Lo 13,000	16,500	3" & 3"	20.049"	20-1/4"	30.129"	27"	18.215"	16-1/4**	16"	25"	68.30%

Standard F	eatures:	5		
2	True Clean Face Design	T		
	• 26,000BTU			
see page	Electronic Ignition	٦		
See page	Ceramic Brick Panel/Black Porcelain Panel			
U	Your Choice of Either: Rock & Glass or			
	Traditional 9pc Log Set			
	100% Safety Shut Off			

Surrounds: (Mandatory) Options: Standard Black Surround w/Safety Screen 26" High Deluxe System 110V Standard Black Surround w/Safety Screen 28" High Premier Battery Powered Standard 4 Sided Black Surround w/Safety Screen



Model	Model BTU's		Vent	Vent Height		Width		Depth		Viewing Area		Efficiency
	Natural Gas	Propane		Actual	Framing	Actual	Framing	Actual	Framing	Height	Width	EnerGuide
OD2000	Hi 40,000	32,500		25"	24"	12 1/0"	47 2/0"	14"	16"			
OD2000	Lo 29,000	24,000	Vent-less	25	31"	43-1/8	47-3/8"	14	16"			

Options:

Standard Fe	eatures:
	Linear Design
	 True Clean Face Or keep trim exposed
	• 40,000BTU
see page 5	All Stainless Steel
see bage s	Crisscross Stainless Steel Burner
	Remote Control
	 White Glass and River Pebble kit
	Cover with Kill Switch

 Driftwood #1,#2, or 3pcs 	
Media Kits	
Ceramic Stones	

